

# SZ4589903 | F11TSV SM MT

HomeConnect® 75 Ohm Coaxial Drop Cable, Series 11, black PVC jacket



## Product Classification

Product Type	Coaxial drop cable
Product Brand	HomeConnect®
Product Series	11 Series
Warranty	One year

## General Specifications

Cable Type	Series 11
Center Conductor Type	Solid
Jacket Color	Black
Jacket Marking	Meters
Shield Construction Type	Trishield

## Dimensions

Diameter Over Center Conductor, nominal	0.064 in   1.626 mm
Diameter Over Dielectric, nominal	0.28 in   7.112 mm
Diameter Over Inner Shield (Tape), nominal	0.287 in   7.29 mm
Diameter Over Jacket, nominal	0.4 in   10.16 mm
Jacket Thickness, nominal	0.039 in   0.991 mm
Center Conductor Gauge	14 AWG
Inner Shield (Braid) Gauge	34 AWG

## Electrical Specifications

Capacitance	16.2 pF/ft   53.15 pF/m
Characteristic Impedance	75 ohm
Characteristic Impedance Tolerance	±3 ohm

# SZ4589903 | F11TSV SM MT

<b>dc Resistance Note</b>	Nominal values based on a standard condition of 20 °C (68 °F)
<b>dc Resistance, Inner Conductor, nominal</b>	12.5 ohms/kft   41.01 ohms/km
<b>dc Resistance, Loop, nominal</b>	17.1 ohms/kft   56.102 ohms/km
<b>dc Resistance, Outer Conductor, nominal</b>	4.6 ohms/kft   15.092 ohms/km
<b>Nominal Velocity of Propagation (NVP)</b>	85 %
<b>Operating Frequency Band</b>	5–3000 MHz

## Attenuation

Frequency (MHz)	Attenuation (dB/100 m)	Attenuation (dB/100 ft)
5.0	1.25	0.38
55.0	3.15	0.96
83.0	3.87	1.18
85.0	3.9	1.19
187.0	5.74	1.75
204.0	6.14	1.87
211.0	6.23	1.9
250.0	6.72	2.05
300.0	7.38	2.25
350.0	7.94	2.42
400.0	8.53	2.6
450.0	9.02	2.75
500.0	9.51	2.9
550.0	9.97	3.04
600.0	10.43	3.18
750.0	11.97	3.65
865.0	13.05	3.98
1000.0	14.27	4.35
1218.0	16.14	4.92
1300.0	16.44	5.01
1400.0	17.13	5.22
1500.0	17.79	5.42
1600.0	18.44	5.62
1700.0	19.08	5.81
1794.0	19.66	5.99
1800.0	19.7	6

# SZ4589903 | F11TSV SM MT

2000.0	20.89	6.37
2200.0	22.05	6.72
2500.0	23.7	7.22
2800.0	25.28	7.71
3000.0	26.3	8.02

## Material Specifications

Center Conductor Material	Copper-clad steel
Dielectric Material	Foam PE
Jacket Material	PVC
Inner Shield (Braid) Coverage	60 %
Inner Shield (Braid) Material	Aluminum
Inner Shield (Tape) Material	Aluminum/Polymer/Aluminum (APA) bonded
Outer Shield (Tape) Material	Aluminum/Polymer/Aluminum (APA)

## Environmental Specifications

EN50575 CPR Cable EuroClass	Eca
Environmental Space	Indoor   Outdoor
Flame Test Listing	IEC 60332-1-2

## Packaging and Weights

Packaging Type	Reel
Weight, gross	67 lb/kft   9.263 kg/km

## Regulatory Compliance/Certifications

Agency	Classification
CENELEC	EN 50575 compliant, Declaration of Performance (DoP) available
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

